

Talk Light

Installation of the Talk Light Stand

Talk Light Stand delivered parts:

1. 8ft. 4inch PVC pole with mounting flange, mounting flange is secured to base for transporting.
2. 24inch X 36inch X 3inch Talk Light base.
3. 4 sets of a 5/8 bolts, washer and nut.
4. 4 - 5 1/2inch hose clamp, to affix Talk Light to the 4inch pole.
5. 4inch pole cap

Building the Stand: The pole is shipped 8ft. long and may be cut to any length. The 4inch pole has been selected to fit the Talk Light arms perfectly. Remove flange from base by removing the bolts and nuts. Place mounting flange on the free end of the pole, flat side down, and slide down until it is flush with the secured end of the pole. Line the flange up with the holes on the base. Push the 4 - 5/8 bolts through the flange and base. Place washer and nut on underside of base. Put all 4 bolts and nuts on before tightening. Tighten Securely.

Installing Talk light to the stand: The Talk Light is held to the pole with 4 - 5 1/2inch hose clamps, (furnished with the Talk Light Stand). Position the Talk Light on the pole at the desired height. Tighten two hose clamps to the top and bottom arms. Make sure the light is straight prior to tightening securely.

Place the pole cap on the pole by hand Pressure.



4 - Hose Clamps shown in insert are used to fasten Talk Light traffic light to pole at any height.

Tighten 4 - Bolts securely.

Phone 877 809 6250

email: support@talklight.com